



### W7 Best Pos System

LB-W7-A Pos System features modern and High cost performance, powerful performance, superior touch display, multiple I/O interfaces and Fast installation.

Simply customized for today's retail and restaurant businesses.

### POS Feature:

- \*Industrial-grade motherboard
- \*15" Industrial Grade A LED (4:3)
- \*Multiple I/O Interfaces for Peripherals
- \*Certification: ROHS/CE/FCC
- \*Fast Installation and Easy Serviceability
- \*Flexible Installation on a Counter or a Wall
- \*15" TFT LCD with LED Backlight, \*Resolution up to 1024 x 768,
- \*PCAP Touch or Optional Resistive Touch

### Touch screen: Tempered glass

- \*Bezel-Free True-Flat Display
- \*Brightness 400cd/ m2
- \*Compact Design for Limited Counter Space

### Optional For pos machine:

1. Main Board CPU: Industrial grade J1900 (optional for J1800, i3, H81, i5, i7)
2. RAM: 2GB, 4GB, 8GB, 16GB
3. Hard Disk: 32G, 64G, 128G, 256G, 512G, mSATA/500GB HDD /SSD, M.2
4. OS: Windows XP/7/8/10, Android 7.1/5.1, 6.0, Linux (Trial Version)
5. Display Screen: Industrial grade 12 inch / 15 inch / 17 inch screen
6. Touch Screen: True Flat capacitive/resistive touch
7. Customer Display: LED 8 / VFD 2\*20 / 12.1" / 15" / 17"
8. Interface: COM\*(2-6), VGA\*1, RJ45\*1, MIC\*1, Audio Output\*1, USB\*(4-6), RJ11, PS/2, LPT, And SO ON, Card reader (MSR, EMV, RFID, Ibutton)

### 9. WIFI, Camera(15.6''), Speaker, Microphone

# W7 Specificaiton

Industrial POS Computer

**IRS**POS

| Specificaiton    |                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------|
| Main Board       | J1900(2.0ghz) Sim one/J1800 2.4GHZ optional/i3/i5/i7                                                        |
| CPU              | Intel Celeron J1900 2.0GHz Quad core                                                                        |
| Memory           | SAMSUNG DDR3-2GB(Up to 4GB/8GB optional )                                                                   |
| Hard Disk        | FORESEE 64GB mSATA (Default)/SSD(UP TO 64G 128GB SSD Dual channel-Toshelloba FISH particle/500GB HDD)       |
| Ethernet         | Default 10/100M (1000M Self-adaption optional)                                                              |
| Interface        | Serial 2                                                                                                    |
|                  | VGA 1                                                                                                       |
|                  | USB 6(2 out of screen right side)                                                                           |
|                  | LAN 1                                                                                                       |
| Display Screen   | 15/ Inch LED Liquid Crystal<br>Resolution Ratio: 1024*768 (with waterproof and dustproof rubber ring inset) |
| Touch Screen     | 15 Inch five threads High-temperature Capacitive/resistive Screen                                           |
| Power Supply     | Notebook Power Supply (12V5A)                                                                               |
| Customer display | vfd220/11.6" 12'optional                                                                                    |
| OS               | windows 7/10 trial version Android                                                                          |
| Color            | black/white/orange/blue/                                                                                    |
| Weight           | 6KG/pc                                                                                                      |
| Packing Size     | 2pcs/carton 61*47*47cm                                                                                      |
| Warranty:        | 2 years                                                                                                     |

