

iRS SP-POS890

New beautiful appearance
 Improved function and performance
 Firmware online updating available
 Avoid to lose data design



Specification:

Print	Printing Method	Thermal Line
	Printing Speed	220mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
Character	Character Set	ASCII, GB18030(Chinese),BIG5
	Print Font	Codepage, ANK: 12 x24; Chinese: 24 x 24
	Character per Line	42/48
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5± 0.5mm
	Paper Roll Diameter	Max: 80.0mm
	Roll Core Inner Diameter	13mm(min.)
	Paper Thickness	0.06~0.08mm
Paper Supply Method		Drop-in easy paper loading
Reliability	MCBF	60 million lines
	TPH	100km
Barcode		1D: UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128, 2D:PDF417,QR CODE, DATA matrix
Emulation		ESC/POS
Driver		Windows/Linux/OPOS
Cash Drawer Control		DC24V,1A 6PIN RJ-11 Socket
Interface		USB+RS-232/USB+Ethernet
Power Supply (Adapter)		AC100 ~240V ± 10%(include) DC 24V, 1.5A
Auto cutter	Type	Guillotine
	Life	1,000,000 cuts
	Cutting Method	Partial cut
Physical	Net Weight	1.3kg
	Gross Weight	2.6kg
	Printer Dimension (WxLxH)	185 x 150x 123 mm (L x W x H)

Product pictures:

188 FILOLAOY str. Athens Greece 11632 Tel: +30 210 75 60 230
Mob: + 30 693 66732 38 Email: sales@tamiaki.gr

